

TSR-2900-20C



Multiservice Switching Router

Product Overview

Techroutes TSR-2900-20C Series is the next-generation multi-functional switching router switching engine. It is a well-adapted router.

Techroutes TSR-2900-20C Series has supports the full switching function, USB2.0 expansion, service expansion and engineering maintenance.

Techroutes TSR-2900-20C Series is equipped with TROS operating system, of which Techroutes has the independent intellectual property right. Techroutes TSR-2900-20C Series builds a real multiservice broadband platform by providing rich software functions such as routing, switching, safety, VPN.

With its strong processing and expansion capability, rich software functions and hardware modules, Techroutes TSR-2900-20C Series meet requirements of the government, financial institutions, the defense system, operators and enterprises in network construction.

Main Characteristics

Powerful Performance

Techroutes TSR-2900-20C Series is driven by the 64-bit dual-core processor with specialized gigabit ASIC switching chip and FPGA components, which enables the whole hardware platform to run on the high-speed Ethernet frame. The innovative design endows TSR-2900-20C with a super processing capability, providing a guarantee for upper-layer software functions.

High Expandability

Because built on the basis of switching core, Techroutes TSR-2900-20C Series can expand their external interfaces, slots and modules without any limitation from the total CPU resources. The switching chip guarantees that the whole Techroutes TSR-2900-20C router is provided with sufficient and broadband internal channels, making the expansibility of Techroutes TSR-2900-20C routers exceed that of traditional modularized routers.

Excellent Power-saving ability

Techroutes TSR-2900-20C Series adopts the new-generation hardware chip in consideration of energy saving while guaranteeing its strong processing capacity. Compared with the mainstream devices in the industry, power consumption of the TSR router is reduced by 15% to 20%, which both reduces the device maintenance cost and accords with the low-carbon idea. Techroutes TSR-2900-20C Series is also equipped with the environment friendly maglev mute fan..

Various Protocol Support

Techroutes TSR-2900-20C Series supports Layer 2 link protocols including PPP and dot1q; static routing; policy routing; and dynamic routing such as RIP, OSPF and BGP. These routing protocols are well compatible with the devices manufactured by the mainstream vendors in the industry. Besides, TSR-2900-20C Series supports integration of multiple services such as routing, switching, voice, safety and wireless, which meets the requirement of complicated network construction.

New Service

Techroutes TSR-2900-20C Series supports the MPLS characteristics and the MPLS-based layer-2/layer-3 VPN technology, which realize the transparent Ethernet transmission service and the flexible enterprise interconnection. Techroutes TSR-2900-20C Series supports IPv6 data forwarding, routing protocols and multicast routing protocols; Techroutes TSR-2900-20C Series also supports the IPv4/IPv6 protocol stack and the interconnection technology, which makes the existing networks smoothly upgrade to IPv6.

Secure Service Access

Techroutes TSR-2900-20C Series supports selective ACL firewall filtration technology, NAT, VPNs such as IPSec/L 2TP/PPTP/GRE, and security technologies such as AAA, Radius, PAP/CHAP.

Traffic management policy

Techroutes TSR-2900-20C Series supports varied queues including FIO, PQ, CQ, CBWFQ, LLQ, WFQ DSCP, IP Precedence, RTS, RSVP and CAR.

Techroutes TSR-2900-20C Series supports its self-developed traffic control and service management policy (GBSC) which can better real-time arrange and monitor your data traffic.

Flexible management and maintenance

Techroutes TSR-2900-20C Series is convenient in managing and monitoring the network by using the in-band and out-band management tools such as Console, Telnet, SSH and SNMP;

Complete Layer-2 Switching Capacity

Techroutes TSR-2900-20C Series supports Layer-2 switching with the built-in high performance switching chip. It supports layer-2 protocols including STP/RSTP/MSTP, MAC learning and filter, anti-attack based on the chip, storm control and port mirroring.

Technical Specification

Model	TSR-2900-20C	
Interface		
Console	1	
USB2.0	1	
WAN	2xGE-TX & 2xGE Combo (TX/SFP)	
LAN	/	
POE	/	
SLOT	/	
RST	1	
Encryption Engine	Built-in	
Performance		
Throughput	3MPPS	
Flash	32MB	
DRAM	1GB	
NAT Concurrent Sessions	<250K	
Consumption	No Load	≤6W
	Full Load	≤10W
Total output BTU (note:1000 BTU/hr=293W)	34.13	
FAN	/	
Noise@25°C (dBA)	0	
Power Supply	100-240VAC	
Software Features		
LAN	ARP, ARP proxy, Gratuitous ARP	
WAN	PPP, PPPoE (Client/Server)	
Routing	Static route, default route	
	RIPv1/v2, OSPFv2, BGPv4,IS-IS	
	Fast Switch, Load-Balance	
	PBR (Policy Based Routing)	
Multicast	IGMP V1,V2,V3	

		PIM-DM, PIM-SM
IPv6		IPv6 ND, IPv6 PMTU, IPv6 FIB, IPv6 ACL, IPv6 (authenticate through IPv6 Phasell)
		IPv6 QoS
		IPv6 transition: NAT-PT, IPv6 tunnel, 4over6
		IPv6 tunnel: IPSec v6, GRE, 6to4,
		ISATAP
		IPv6 route: IPv6 static route, RIPng, OSPFv3, BGP4+
MPLS		VPLS, MP-BGP, VRF
		L2VPN, L3VPN
IP Service		ICMP, TCP, UDP, IP Option
		NAT, PAT, Port-MAP, Private- Service, ALG
		Ping, Trace Route, Nslookup
		IP ACL, IMP filter, Fast-Access
		DHCP Client/Serv/Relay
		DNS, DNS host, DNS Proxy, DDNS (Peanut Hull/DynDNS/CTC)
		Helper-Address, UDP Helper
		IP unnumber, DDR
		Keep alive, PDP (compatible with CISCO)
		NetFlow, IP Accounting, IP SLA
		TFTP Client/Serv, FTP Client
		SNTP/NTP, job/schedule
		PNP
		ALIAS
	Reverse telnet, VTY binding	
Switching		802.1p CoS, 802.IQ VLAN
		STP, RSTP
		Keep alive, port mirror, broadcast/ multicast storm control
		PTP, IEEE1588v2 (Optional)
Network Safety	AAA	Authentication, Authorization, Accounting
		enable, local, Radius, Tacacs+
		PAP, CHAP, MS-CHAP
Network Security	Firewall	ACL, NAT
		ASPF state detection
		SYN flood, UDP flood or ICMP flood
		ARP attack protection, ARP-SCAN and DHCP-Snooping
		Prevention of Ping of Death, Tear-drop, Land-Based, WinNuke, PingSweep, ARP attack and IP-Spoofing
	VPN	IKE, IPSec, DMVPN, EZVPN
		L2TP, PPTP, GRE, EoGRE
VPN Stacking		

Reliability	Backup Function	Interface backup
		Route backup
		E-Backup, Keep alive Ethernet remote monitoring
		VRRP, HSRP
		Bandwidth based load sharing and backup
	Traffic based load balancing and backup	
	BFD	BFD for RIP, OSPF, BGP, MPLS and VRRP
QOS	Congestion management	FIFO, PQ, CQ, WFQ, CBWFQ
	Congestion avoidance	WRED/RED
	Traffic shaping	GTS (Generic Traffic Shaping)
	Others	GBSC, Layer7filter
	Traffic classification	ACL
		IP Precedence
		DSCP
		MAC
		802.1p
Management		Console, Telnet, SSH,HTTP/HTTPS,SSL
		SNMP V1/V2/V3, SYSLOG, RMON, ZTP
Appearance		
Chassis	Dimensions mm (WxDxH)	300x200x44
	Weight (kg,empty)	1.7
Package	Dimensions mm (WxDxH)	454x287x96
	Weight (kg)	2.7
Environmental Specifications		
Operating	Temperature	-10°C~50°C
	Humidity	5%~95% (non-condensing)
Storage	Temperature	-40°C~85°C
	Humidity	5%~95% (non-condensing)
Accessories		
Console cable, Rack mount kits, Manual		
Certificate		
CE, FCC, RoHS, ISO		

Order Information:

TSR-2900-20C	TSR-2900-20C Multi-service Router (1 Console, 1 USB2.0, 2xGE TX, 2xGE Combo (TX/SFP),built-in encryption engine, AC power supply)
TSR-2900-20C-DC	TSR-2900-20C-DC Multi-service Router (1 Console, 1 USB2.0, 2xGE TX, 2xGE Combo (TX/SFP),built-in encryption engine, DC power supply)

Copyright ©Techroutes Network Pvt Ltd. 2020. All Rights Reserved. This document is Techroutes Network Public Information. Techroutes Network reserves the right to alter, update and otherwise change the information contained in the document from time to time.



For More details:

visit: www.techroutes.com

Or contact

sales@techroutes.com

info@techroutes.com