

TR-S3954-P Switch



10 G Layer 3 POE Switch

Product Overview:

Techroutes TR-S3954-P is a new generation of aggregation 10G switches introduced by Techroutes Network Pvt Ltd. It is targeted at the IP MAN (metropolitan area network), campus networks and enterprise networks. It is developed on the basis of high performance hardware and TRROS – software platform with Techroutes own independent intellectual property rights. It supports multiple services like IPv6, MPLS, VPN and network security based on L2/L3/L4 wire-speed switching service. It also supports nonstop upgrade, continuous forwarding, graceful restarting and redundancy protection. It supports up to 48 gigabit ports and 6 10GE ports.

Product Characteristics:

Carrier-Level QoS Policies

Supports priority retagging and complicated flow classification based on VLAN, MAC, source address, destination address, IP or priority to better streamline carrier's services. Supports flexible bandwidth control policies and supports port-/flow based flow limit, and ensuring the line speed forwarding of each port to make sure the high quality of video, audio and data services. Supports 8 priority queues by each port. Supports multiple queue schedule algorithms such as SP, WRR, or "P plus WRR"

Innovative Virtual Cluster Switching Technique TVSS (Techroutes Virtual Switch System):

Virtualize multiple physical devices into one. The performance, reliability and management of the virtual system are superior to the physical ones;

Improved Performance: TRVSS makes full use of each link in the physical devices, which avoids STP blocking the link and protects the original link to the maximum extent;

High Reliability: Based on the advanced distribution mechanism and efficient cross-physical link aggregation link function, the logic control plane, service control plane and service data plane are separated. Thus, the device can support continuous layer3 routing forwarding, avoiding service interruption as a result of a single point of failure; **Easy Management:** TRVSS realizes single IP management, greatly improving the networking efficiency and lowering the operating cost.

Easy Management: TRVSS realizes single IP management, greatly improving the networking efficiency and lowering the operating cost.

Versatile IPv6 Solution

TR-S3954-P supports the IPv6 protocol suite, IPv6 neighbour discovery, ICMPv6, path MTU discovery, DHCPv6, etc.; TR-S3954-P supports Ping, Traceroute, Telnet, SSH, ACL based on IPv6; TR-S3954-P supports MLD, MLD Snooping, IPv6 static routing, RIPng, OSPFv3 and BGP4+, etc.; Supports IPv6 tunnel: manual tunnel, automatic tunnel, GRE tunnel, 6to4 tunnel, ISATAP; TR-S3954-P supports IPv4 transiting to IPv6: IPv6 manual tunnel, automatic tunnel, 6 to 4 tunnel, ISATAP tunnel.

Varied Service Characteristics

Supports layer-2 and layer-3 multicast routing protocol, which enable the device can access to IPTV, HD video surveillance and HD video conference. Supports layer-3 routing protocol and super-large routing table capacity, which enables the device is available in large campus networks, enterprise networks and industry networks. Supports MPLS multi-VRF and layer-2 VPN.

Industrial Ethernet Ring with Zero Delay and Zero Packet Loss.

Supports industry-level EAPS and ERPS, and their protection recovery time is less than 50ms. Their high reliability is represented by the null packet loss, which has been proved by many years of application in the Grid, rail transportation and defense systems.

Complete Security Mechanism

Equipment-Level Security: The advanced hardware infrastructure design realizes the level-based packet schedule and packet protection, prevents DoS-/TCP related SYN Flood, UDP Flood, Broadcast Storm or large traffic attacks, and supports level-based command line protection, endowing different levels of users with different management permissions. Security Authentication Mechanism: IEEE 802.1x, Radius and TRTacacs+ Enhanced Service Security Mechanism: supports the plaintext or MD5 authentication of relevant routing protocol, URPF, deep inspection of hardware packet, control packet and data packet and filtering technology.

Innovative Energy-Saving Design

Intelligent power management: The power system of TR-S3954-P supports real-time monitoring the device and the slow-start. It is also power-saving. Intelligent fan management system: The fan systems of TR-S3954-P supports automatic speed regulation, which efficiently slow the fan speed and mitigate the noise. Complies with the international standard IEEE 802.3a.

Flexible and Convenient Management and Maintenance

Supports management modes such as the console port, Telnet, SSH, etc. Supports the WEB management mode, which is easy and efficient so that it makes installation and debugging convenient. Supports TFTP-patterned file upload/download management. Supports ISSU (In-Service Software Upgrade).

Intelligent PoE+

TR-S3954-P supports IEEE 802.3af/at PoE standard, and power mapping scales up to a maximum of 760W of PoE+ power; TR-S3954-P supports PoE non-stop power supply. The PoE+ power is maintained during a switch reload; TR-S3954-P supports manual and dynamic PoE power allocation; TR-S3954-P supports up to 6KV thunder-proof of the PoE port and power supply;

Technical Specification

Item		TR-S3954-P
Interface		48xGE TX ports,6x10GE/GE SFP+ ports
Console		1 RJ45 console
Backplane		216 Gbps
Forwarding rate		162 Mpps
Chassis	Dimensions(Wx DxH)(mm)	440x350x44
Package	Dimensions(Wx DxH)(mm)	576x448x94
Power consumption	Full Load	≤1000W(POE) W
Power supply (hot-swap)	AC: 100V-240V,50Hz±10%	Support
Total output BTU (1000BTU/H=293W)		3412.96
Noise@25°C (dBA)		45
MTBF(H)		>200,000
Forwarding mode		Store-forward
Flash (MB)		16
DRAM (MB)		512
MAC		32K
Buffer Size(MB)		2
Jumbo frame		9K
Routing table	IPv4	12K
	IPv6	6K
ARP table	IPv4	12K
	IPv6	2K
Total SVI		1K
VLAN		4K Active VLAN, QinQ & Selective QinQ, GVRP, Voice VLAN
Spanning Tree		802.1D (STP), 802.1W (RSTP) and 802.1S (MSTP)
		BPDU guard, root guard and loopback guard
Multicast		PIM-SM, PIM-DM, IGMP v1/v2/v3, IGMP Snooping, IGMP Fast Leave, MVR, IGMP filter
IPv4		Static routing, RIP v1/v2, OSPF, BGP, PBR, ECMP
		BFD for OSPF, BGP

IPv6	ICMPv6, DHCPv6, ACLv6 and IPv6 Telnet
	IPv6 neighbor discovery, Path MTU discovery
	MLD V1/V2, MLD snooping
	IPv6 Static Routing, RIPng, OSPFv3, BGP4+
	Manual tunnel, ISATAP tunnel, 6 to 4 tunnel
MPLS	Multi-VRF
QoS	CAR, HQoS, MAC/IP/TCP/UDP/VLAN/COS/DSCP/TOS based QoS, 802.1P/DSCP
	priority re-labeling, SP, WRR, and "SP+WRR", Tail-Drop, WRED, flow monitoring and
	traffic shaping
Security	Port isolation, Port security, and "IP+MAC+port" binding, MAC sticky DHCP
	Snooping and option 82, DAI & IP source guard, PPPoE+,
	IEEE 802.1x, Radius and Tacacs+
	L2/L3/L4 ACL flow identification and filtration Anti-attack from DDoS, TCP's SYN
	Flood, UDP Flood, etc. Broadcast/multicast/unknown unicast storm-control
	MD5, SHA-256, RSA-1024, AES256, etc.
Reliability	Static/LACP link aggregation, Interface backup
	TRVSS virtual-stacking
	EAPS and ERPS
	URPF, LLDP,ISSU
	VRRP
	1+1 power backup
Management	Console, Telnet, SSH v1/2, HTTP, HTTPS
	SNMP v1/v2/v3, RMON
	TFTP, FTP, SFTP
	NTP, SPAN, RSPAN,SFlow
Environment	Operating temperature/humidity: 0°C -50°C ,10%-90% non-condensing
	Storage temperature/humidity: -20°C -70°C , 5%-95% non-condensing

Product Order Information:

Item	Description
TR-S3954-P	Ethernet routing switch with 48 GE POE and 6 10GE ports (1 RJ45 console port, 48 GE POE TX ports, 6 10GE/GE SFP+ ports; 2 power slots with 1 hot-swap AC220V power supply; the cooling fan, 1U, standard 19-inch rack-mounted installation)
PWR-500-AC	Hot-swap power supply of TR-S3954-P POE (500W max power, 380W max POE power, AC100~240V input, the isolated cooling fan)

Copyright ©Techroutes Network Pvt Ltd. 2023. All Rights Reserved. This document is Techroutes Network Public Information. Techroutes Network reserves the right to alter, update and otherwise change the information contained in the document from time to time.



For More details:

visit: www.techroutes.com

Or contact

sales@techroutes.com

info@techroutes.com