

TR-2005-5G



5G Industrial Router

Product Overview

Techroutes TR-2005-5G router is a compact, Gigabit Ethernet, ruggedized 5G/4G/3G dual cellular networking solution designed for mission-critical connectivity in the most challenging environments. It is qualified for M2M (Machine to Machine), IoT (Internet of Things) and In-Vehicle applications. Super mini size suitable for embedding applications.

In addition to the robustness, reliability, security, friendly-using, the TR-2005-5G is competent to be engineered to protect against extreme temperatures, humidity, shocks, vibrations, reverse polarity, and transient voltage, which is widely used in more than twenty industrial fields, such as CCTV security surveillance, AMR, vehicle, retails, vending machines, power control, water schedule, traffic, oil field, weather forecast, environmental protection, street lamp control, post, bank and many other fields.

Technical Specification

TR-2005-5G	
Compatible Mobile Networks	5G (SA and NSA)
	4G LTE (FDD/TDD)
	3G UMTS WCDMA (HSUPA/HSDPA/HSPA/HSPA+/DC-HSPA+)
Cellular Frequency	5G NR SA: n1/n28/n41/n78/n79
	5G NR NSA: n41/n78/n79
	TDD LTE:B34/ B38/ B39/ B40/ B41
	FDD LTE:B1/B3/B5/B8
Hardware	UMTS/HSPA/HSUPA/HSPA/HSPA+: B1/B8
	CPU: 880Mhz dual core
	Flash: 128Mb up to 8G
WAN	RAM: 1G up to 4G
	2x Cell Interface (5G/4G/3G) SIM Card Slot (Active/Passive)
	Support 1.8V/3V UIM/SIM cards, E-SIM is supported
LAN	1x 10/100/1000M WAN Port RJ45 Interface
	2x10/100/1000M LAN Port RJ45 Interface, 2x10/100M LAN Port RJ45 Interface
Wi-Fi	802.11a/b/g/n 802.11ac Optional
	Single Band, Dual-Band & Dual-Concurrent Optional
	AP and client
	Up to 64 connected devices (64 per channel – 2.4 GHz and 5 GHz)
Serial connector	WPA2 Enterprise (Wi-Fi),Hotspot/Captive Portal, SSID-based Priority
	RS232 (Terminal Socket)
DI/DO	4 Digital I/O ports (Terminal Socket) Optional
USB	USB 3.0 Interface
SMS,SMS Control and Alarm	Receive and Send the SMS
	WAN Cell APN configuration via SMS
Features	SMS/Voice Control and Alarm. SMS or Call to control router to be online, offline, reboot, signal and status monitor; SMS is default feature, SMS text sending and receiving
	WAN ports support Cell/Static IP/DHCP/PPPoE (on demand, keep alive, schedule, manual, standby)
	Failover/Failback and Load Balance
	Advanced Modem Failure Check
	IP Pass through
	WiFi as WAN
	DHCP Server, Client, Relay
	DNS and DNS Proxy
	DDNS
	Syslog
	NTP
	UPnP

	DMZ
	Multicast/Multicast Proxy
	QoS (DSCP and Priority Queuing)
	MAC Address Filtering
	VLAN 802.1Q
Routing	Static
	Dynamic (OSPF/BGP/RIP)
	Virtual Server/Port Forwarding
	IPv6
	VRRP
VPN	IPSec – Tunnel, NAT-T, and transport modes; IKEv1 & IKEv2
	Hash (MD5, SHA128, SHA256, SHA384, SHA512), Cipher (AES, 3DES, DES)
	GRE tunneling
	PPTP support
	L2TP, L2TP over IPSec support
	VPN pass-through
	Open VPN support (option)
	DMVPN (option)
	Certificate support (option)
	Multiple networks supported in a single tunnel, site-to-site dynamic VPN with NHRP; VTI Tunnel support
Optimized IP Communication	WAN Affinity and QoS allow prioritization of VoIP services
	Advanced VPN connectivity options to HQ
	SIP ALG and NAT to allow VoIP and UC communications to traverse firewall
	802.1p/q for LAN QoS segmentation and treatment of VoIP on LAN
	Private Network support (wired & 5G/4G/3G WAN)
Security	RADIUS and TACACS+ support (Optional)
	802.1x authentication for Ethernet
	Certificate support
	ALGs
	MAC Address Filtering
	Advanced Security Mode (local user management only)
	Per-Client Web Filtering
	IP Filtering
	Content Filtering (basic)
	Website Filtering
	Zone-Based Object Firewall with host address (IP or FQDN), port, and mac address
	Other Details: NAT, SPI, port blocking, service filtering (FTP, SMTP, HTTP, RPL, SNMP, DNS, ICMP, NNTP, POP3, SSH), protocol filtering, WAN ping (allow/ignore)
Management	GUI

	Telnet
	SSH
	SNMP V1/V2/V3
	SMS control
	TR-069 (optional)
	Reset Button
	Techroutes Net view NMS
Firmware upgrade	Support firmware update locally, remotely (LAN, WiFi and OTA WAN) and NMS (Network Management System) option
Antenna	2 cellular antenna connectors (SMA)
	4~6 Wi-Fi antenna connectors (SMA)
	1 GPS antenna connector (SMA)
Led	SYS, ERR, VPN, WiFi, USB, WAN, LAN*4, SIM1 Online, SIM2 Online, Signal1, Signal2, Signal3
Power supply	Power (DC Jack, 2 Pin Terminal Block for wire connection) Input Voltage range: 5-40 VDC / 5-60VDC option, 12VDC 2A adapter recommended
	Built-in transient and reverse polarity voltage protection
Operating Temperature	Storage: (-40°C to 85°C)
	Working: (-35°C to 75°C)
Humidity	5% to 95% operating
	5% to 95% storage
Dimensions	(L x W x H): 132mm x 112mm x 45mm
Weight	About 410g (Without accessories)
	About 850g (With accessories)
Case	Metal Gray-Black
	Wall Mount/Desktop

Order Information :

Product	Description
TR-2005-5G	Techroutes 5G Industrial Router (2xCell Interface (5G/4G/3G),1xGigabit Ethernet WAN Interface, 2xGigabit Ethernet Interface & 2xFast Ethernet Interface LAN, Power Adapter)

Copyright ©Techroutes Network Pvt Ltd. 2023.All Rights Reserved. This document is Techroutes Network Public Information. Techroutes Network reserves the right to alter, update and otherwise change the information contained in the document from time to time.

**For More details:**

Visit: www.techroutes.com

Or contact

sales@techroutes.com

info@techroutes.com