

TR-IES-3936



Industrial Grade Gigabit Ethernet Switch

TR-IES-3936 is 36-port industrial grade fully managed Layer 3 Ethernet switches, which supports auto negotiation, Offers 24xGigabit Ethernet ports, 8xGigabit SFP Ports, 4x10G SFP+ Ports. Its plug and play, designed in wide operating temperature from -40°C to 75°C, with performance of dust/salt fog proof, make it completely suitable for harsh environments.

Technical Specification

	TR-IES-3936
Ports	24x10/100/1000BaseT RJ45 Ports, 8x1G SFP Ports, 4x10G SFP+ Ports, console port
Backplane	144Gbps
Forwarding	Full wire-speed filtering and forwarding, Packet forwarding rate: 107 Mpps
Packet Buffers	32Mbit
Switching Delay	<5μS
Switching	Store forwarding
MAC table	32K
Flow control	IEEE802.3x flow control, back pressure flow control
IPv4/Ipv6	Support
Jumbo Frame	9K
Mirror	Port mirroring, port speed limit
Storm control	Broadcast and multicast storm control
Multicast	IGMP v1/v2/v3 Snooping, MLD v1/v2Snooping
QoS	IEEE802.1p 8 active priorities queues for per port, IEEE802.1p based CoS, IP Precedence based CoS, IP DSCP based CoS
Traffic Classification	QCL(QoS Control List): MAC Access control list (Source/Destination MAC, Ether type, Priority ID/ VLAN ID)
Bandwidth	Rate in steps : 100 kbps

control for Ingress	Range : 100 kbps to 1Gbps Rate Unit : bit
Bandwidth control for Egress	Rate in steps : 100 kbps Range : 100 kbps to 1Gbps Rate Unit : bit Per queue shaper
Aggregation	LACP/Link Aggregation Static
Protocol Standard	IEEE802.3i/802.3u/802.3z/802.3x/802.3ad/802.1p/802.1q/802.1d/802.1w/802.1s/802.1ad/802.3az/802.1x/802.1ab
Spanning Tree	STP/RSTP/MSTP/TR-Ring/lpv4/lpv6
IEEE 1588PTP	Support (Optional)
Routing	Static, RIP,OSPF,BGP
Redundancy	VRRP
Ring Protection	Support ITU-TG.8032 Ethernet Ring protection
VLAN	IEEE802.1Q VLAN/MAC based VLAN/Protocol based VLAN /IP subnet based VLAN/Q-in-Q/GVRP/MVR,IEEE802.3ac VLAN tagging
VLAN table	4K
Management	Web, CLI, Telnet, SSH, SNMPv1/v2/v3, RMON/System syslog/NTP
Secure Channel	Secure channel by SSL/SSH, FTP, DAI, LAG, GUI, LLDP, LLDP-MED
Network security	Port-based IEEE802.1X/Single and multiple IEEE802.1X/MAC-based authentication/VLAN Assignment/ IP source guard/RADIUS/TACACS+/ACL/SSHv2/HTTPS
DNS	DNS client/proxy
DHCP	DHCP Server/Client/Relay/snooping
Size	440×335×44mm
Shell	Metal, Fan less, IP40 protection level
Weight	3.5Kg
Installation	1U Rack
EMI	FCC Part15 Class B, EN50155,EN50121,EN55022,EN55024
EMS	IEC61000-4-2(ESD)Level3,IEC61000-4-3(RS)exceeds Level 3,IEC61000-4-4(EFT)Level3,IEC61000-4-5(Surge)Level3,IEC61000-4-6(CS)Level 2,IEC61000-4-8,IEC61000-4-11,IEC61000-4-16
Mechanical	Vibration:IEC60068-2-6, Impact:IEC60068-2-27, Falling:IEC60068-2-32
Power Input	DC: 48V
Power Redundancy	Yes (Optional)
Power Connection	5 Pin 5.08mm block terminal
Alarm Connection	3 Pin 3.81mm block terminal
Power Protection	Reverse connection protection, Over voltage protection, Over current protection, Alarm output
Rated Power	≤40W
Indicator	Power: P1, P2,Alarm:A, Run system/Ring: Connector: Link/Act, Speed (RJ45), Link/Act(SFP)
Environment	Operating Temperature: -40℃~75℃

Storage Temperature: -40°C~85°C Relative Humidity: 5~95%non condensing

Order Information:

TR-IES-3936-P	Industrial Ethernet switch (1 console port, 24x10/100/1000M RJ 45 Ports,8xGigabit SFP Ports,4x10G SFP+ Ports, RJ 45 connector RS232 TX/RX, 48VDC Power Input)
---------------	---

Copyright ©Techroutes Network Pvt Ltd. 2022. All Rights Reserved. This document is Techroutes Network Public Information. Techroutes Network reserves the right to alter, update and otherwise change the information contained in the document from time to time.



For More details:

visit :www.techroutes.com or contact
sales@techroutes.com
info@techroutes.com