

## TR-S5700 Series

### 2.5 Gigabit Ethernet Switch Series



#### Product Overview

TR-S5700 series is a Techroutes-developed multi-gigabit Ethernet switch oriented for the next-generation IP metropolitan area network, large campus network, and enterprise network. TR-S5700 series adopts the cutting-edge hardware architecture and is equipped with the TROS operating system with Techroutes independent intellectual property rights. On the basis of providing high-performance L2/L3/L4 wire-speed switching services, TR-S5700 series further integrates various network services such as IPv6, MPLS VPN and network security. Combined with multiple high-reliability technologies such as uninterrupted upgrade, uninterrupted forwarding, graceful restart, and redundancy protection, TR-S5700 series ensures the long-term stable communication capability of the network.

TR-S5700 series has a variety of product specifications, supporting 48/24/8 2.5G access, 10G/40G high-speed uplink ports.

TR-S5700 series is widely used in high-end cyber cafes, E-sports hotels, and high-speed enterprise network.

#### Product Characteristics

##### Advanced hardware architecture, cutting edge processing capability

TR-S5700 series 1U pizza-box switch realizes the ultra-high port density of 48 2.5G TX ports, 4 10G SFP+ ports, and 2 40G QSFP ports. Equipped with high-performance ASIC switch chips, TR-S5700 series can meet the application requirements of various complex scenarios.

##### Innovative VSS

TR-S5700 series supports innovative Techroutes Virtual Switch System, which can virtualize multiple physical devices into one logical device with unparalleled performance, reliability, and management compared to stand-alone physical devices.

**Doubled performance:** The virtualized system makes full use of every link between physical devices, avoiding the link congestion of the traditional networking model Spanning Tree Protocol, making the best use of devices, doubling the performance, and protecting the original link investment to the greatest extent.

**High reliability:** Based on advanced distributed processing technology, the efficient cross-physical device link aggregation function separates the logical control plane, service control plane and service data plane, providing uninterrupted Layer 3 routing and forwarding and avoiding business interruption caused by the single failure. Therefore, the reliability of the virtual system is greatly improved.

**Easy management:** The entire virtual system realizes unified management of a single IP, and physical devices are visible to users, which simplifies the management of network devices and network topology, greatly improves operation efficiency, and effectively reduces operation and maintenance costs.

### Carrier-level high reliability

Based on Hitless Protection System (HPS), the key components of the S5700 series, such as power supply modules, are redundant backup and hot-swappable, which supports seamless switchover in case of failure without manual intervention.

TR-S5700 series supports STP/RSTP/MSTP, VRRP, ring network protection, dual uplink active/standby link protection, LACP and other simple and efficient redundancy protection mechanisms.

TR-S5700 series supports In-Service Software Upgrade (ISSU), ensuring the unremitting data forwarding during system upgrade.

The ultra-high-precision BFD mechanism, through linkage with Layer 2 and Layer 3 protocols, realizes millisecond-level fault detection and service recovery, which greatly improves the reliability of the network system.

Perfect Ethernet OAM mechanism, supporting 802.3ah, 802.1ag and ITU-Y.1731, realizes rapid detection and location of faults through real-time monitoring of network operation status.

The high reliability hardware and software of the TR-S5700 series meet the fault recovery time requirement of 50ms for carrier-level services, and truly achieve the high reliability (99.999%) of carrier-class core devices.

### Rich service features

Perfect Layer 2 and Layer 3 multicast routing protocols meet the access requirements of IPTV, multi-terminal high-definition video surveillance and video conferencing;

Complete Layer 3 routing protocols and large routing table capacity meet the needs of various network interconnection, and can built up ultra-large campus network, enterprise network and industry private network.

Comprehensive Layer 2 and Layer 3 MPLS VPN can built up a super-large MPLS VPN core network to meet the access needs of industry private network VPN users and enterprise network VPN users.

### Comprehensive IPv6 Solutions

Supports the IPv6 protocol suite, IPv6 neighbor discovery, ICMPv6, path MTU discovery, DHCPv6, etc.

Supports Ping, Traceroute, Telnet, SSH, ACL and so on, meeting IPv6 networks' device management and service control requirements.

Supports IPv6 multicast features such as MLD, MLD Snooping, IPv6 static routing, IPv6 Layer 3 routing protocols such as RIPng, OSPFv3, BGP4+, providing complete IPv6 Layer 2 and Layer 3 solutions.

Supports a wealth of IPv4 to IPv6 transition technologies, including: IPv6 manual tunnel, automatic tunnel, 6to4 tunnel, and ISATAP tunnel to ensure the smooth transition from IPv4 network to IPv6 network.

### Perfect Security Mechanisms

Equipment-level security: The advanced hardware infrastructure design realizes the level-based packet schedule and packet protection, prevents DoS-/TCP-related SYN Flood, UDP Flood, Broadcast Storm or large traffic attacks, and supports level-based command line protection, endowing different levels of users with different management permissions.

Perfect security authentication mechanisms: IEEE 802.1x, Radius and TACACS+.

Enhanced service security mechanism: Supports clear text or MD5 authentication of related routing protocols, and Unicast Reverse Path Forwarding (uRPF), which can effectively control illegal services; supports in-depth detection and filtering of control packets and data packets, thereby effectively isolating illegal data packets and improving the security of the network system.

## Technical Specifications

| Item                              | TR-S5754                                                         | TR-S5730            | TR-S5712            |
|-----------------------------------|------------------------------------------------------------------|---------------------|---------------------|
| Console                           | 1 RJ45                                                           | 1 RJ45              | 1 RJ45              |
| Switching capacity                | 480Gbps                                                          | 240Gbps             | 120Gbps             |
| Forwarding rate                   | 360Mpps                                                          | 180Mpps             | 90Mpps              |
| Service port                      | 48x2.5G/GE TX ports                                              | 24x2.5G/GE TX ports | 8x2.5G/GE TX ports  |
|                                   | 4x10G/1G SFP+ ports                                              | 6x10G/1G SFP+ ports | 4x10G/1G SFP+ ports |
|                                   | 2x40G QSFP ports                                                 | N/A                 | N/A                 |
| Chassis Dimensions (WxHxD) mm     | 440*180*44 (mm)                                                  | 440*280*44 (mm)     | 280*180*44 (mm)     |
| Package Dimensions (WxHxD) mm     | 576*448*94 (mm)                                                  | 576*448*94 (mm)     | 350*268*94 (mm)     |
| Power supply                      | AC: 100V-240V,50Hz±10%                                           |                     |                     |
|                                   | DC: -36V~-72V                                                    |                     |                     |
|                                   | Hot-swappable dual-power redundant hot-standby                   | N/A                 | N/A                 |
| Power Consumption                 | <100W                                                            | <48W                | <35W                |
| Environment requirement           | Operating temperature/humidity: 0°C-50°C, 10%-90% non-condensing |                     |                     |
|                                   | Storage temperature/humidity: -20°C-70°C; 5%-95% non-condensing  |                     |                     |
| Total output BTU (1000BTU/H=293W) | 341.30                                                           | 163.82              | 119.45              |
| Noise@25°C(dBA)                   | 55                                                               | 45                  | 45                  |
| MTBF(H)                           | >200,000                                                         | >200,000            | >200,000            |
| Forwarding mode                   | Store-forward                                                    | Store-forward       | Store-forward       |
| Flash                             | 4(GB)                                                            | 16(MB)              | 16(MB)              |
| DRAM (GB)                         | 2(GB)                                                            | 512(MB)             | 256(MB)             |
| MAC                               | 64K                                                              | 32K                 | 16K                 |
| Buffer size (MB)                  | 4.5                                                              | 2                   | 1.5                 |
| Jumbo frame                       | 16K                                                              | 9K                  | 9K                  |
| Routing table                     | IPv4                                                             | 16K                 | 8K                  |
|                                   | IPv6                                                             | 8K                  | 4K                  |
| ARP table                         | IPv4                                                             | 16K                 | 12K                 |
|                                   | IPv6                                                             | 8K                  | 2K                  |
| Total SVI                         | 1K                                                               | 1K                  | 63                  |
| MAC exchange                      | Static configuration and dynamic MAC learning                    |                     |                     |
|                                   | MAC browsing and removal                                         |                     |                     |
|                                   | Configurable aging time of the MAC address                       |                     |                     |
|                                   | Limited number of learnable MAC addresses                        |                     |                     |
|                                   | MAC filtration                                                   |                     |                     |
|                                   | Black hole MAC entry                                             |                     |                     |


|                                        |                                                                                                     |
|----------------------------------------|-----------------------------------------------------------------------------------------------------|
| VLAN                                   | 4K VLAN                                                                                             |
|                                        | GVRP                                                                                                |
|                                        | 1:1 and N:1 VLAN Mapping                                                                            |
|                                        | Basic QinQ                                                                                          |
|                                        | Flexible QinQ                                                                                       |
|                                        | Private VLAN                                                                                        |
| STP                                    | 802.1D (STP), 802.1W (RSTP), 802.1S (MSTP)                                                          |
|                                        | BPDU protection, root protection, loop protection                                                   |
| Multicast                              | IGMP v1/v2/v3                                                                                       |
|                                        | IGMP Snooping                                                                                       |
|                                        | IGMP Fast Leave                                                                                     |
|                                        | Multicast group policy and multicast number limit                                                   |
|                                        | Multicast filtering                                                                                 |
|                                        | Multicast group policy and quantity limitation                                                      |
|                                        | MVR                                                                                                 |
|                                        | IGMP snooping in certain port and VLAN                                                              |
|                                        | Support for transparent passing of multicast traffic without IGMP snooping in certain port and VLAN |
|                                        | PIM-SM/DM/SSM                                                                                       |
|                                        | IPv4                                                                                                |
| Policy Based Routing (PBR)             |                                                                                                     |
| ECMP                                   |                                                                                                     |
| BFD for static routing, RIP, OSPF, BGP |                                                                                                     |
| DHCP                                   | DHCP server, client, relay, snooping                                                                |
| IPv6                                   | IPv4/IPv6 dual Stack                                                                                |
|                                        | ICMPv6, DHCPv6, ACLv6, IPv6 Telnet                                                                  |
|                                        | IPv6 Neighbor discovery                                                                             |
|                                        | Path MTU discovery                                                                                  |
|                                        | MLD v1                                                                                              |
|                                        | MLD Snooping                                                                                        |
|                                        | IPv6 static routing, RIPng, OSPFv3, BGP4+                                                           |
|                                        | Manual Tunnel, ISATAP Tunnel, 6to4 Tunnel                                                           |
| QoS                                    | Traffic classification of port/L2~4 protocol headers/VLAN/CoS/DSCP                                  |
|                                        | CAR traffic control                                                                                 |
|                                        | 802.1P/DSCP priority mapping and remark                                                             |
|                                        | Multiple queuing algorithms such as SP, WRR or SP+WRR                                               |
|                                        | Tail-Drop and WRED                                                                                  |
|                                        | Traffic supervision and traffic shaping                                                             |
| Security                               | 8 queues per port                                                                                   |
|                                        | DDoS attack prevention, TCP-SYN/UDP/ARP Flood attack prevention                                     |
|                                        | IEEE 802.1x authentication, multiple-user authentication, guest vlan                                |
|                                        | L2~L4 ACL                                                                                           |
|                                        | Anti-DOS/IP spoofing/TCP/ping/SYN/ICMP flood attacks                                                |

|                  |                                                             |
|------------------|-------------------------------------------------------------|
|                  | Broadcast/multicast/unknown-unicast storm-control           |
|                  | Port isolation                                              |
|                  | Port Security, MAC address limitation, IP+MAC+ port binding |
|                  | DHCP Snooping, DHCP Option 82                               |
|                  | DAI (Dynamic ARP Inspection)                                |
|                  | IPSG (IP Source Guard)                                      |
|                  | IEEE 802.1x certification                                   |
|                  | MAC-based authentication AAA                                |
|                  | Radius, TACACS+                                             |
|                  | Multiple user privileges                                    |
| Reliability      | 802.3ad Static/LACP link aggregation                        |
|                  | EAPS                                                        |
|                  | G.8032 ERPS                                                 |
|                  | ISSU                                                        |
|                  | VRRP                                                        |
|                  | VSS virtual stacking system                                 |
|                  | GR for OSPF and BGP                                         |
|                  | BFD for OSPF and BGP                                        |
| Management       | CLI, Console, Telnet, SSHv1/2                               |
|                  | Web-GUI: HTTP, HTTPS/SSL                                    |
|                  | SNMP v1/v2c/v3, RMON, SNMP alarm/inform/traps               |
|                  | Upload and download of FTP/TFTP/SFTP files                  |
|                  | Debugging                                                   |
|                  | Syslog for alarm/notification/command/debug                 |
|                  | NTP                                                         |
|                  | SPAN, RSPAN (1:1 and N:1 mirror)                            |
|                  | LLDP, LLDP-MED                                              |
|                  | sFLOW                                                       |
|                  | ZTP (Zero Touch Provisioning)                               |
|                  | Optical DDM                                                 |
|                  | Ethernet cable diagnosis                                    |
| 802.3ah, 802.1ag |                                                             |
| Green technology | IEEE 802.3az EEE (Energy Efficient Ethernet)                |

## Ordering Information

| Techroutes TR-S5700 Series |                                                                                                                                                                                                                                                                           |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item                       | Description                                                                                                                                                                                                                                                               |
| <b>TR-S5712</b>            | Multi-Gigabit Ethernet routing switch with (1 RJ45 CLI port, 8x2.5G/GE TX ports, 4x 10G/GE SFP+ ports; built-in AC220V power supply, 1U, standard 19-inch rack-mounted installation)                                                                                      |
| <b>TR-S5730</b>            | Multi-Gigabit Ethernet routing switch with (1 RJ45 CLI port, 24x2.5G/GE TX ports, 6 10G/GE SFP+ ports; built-in AC220V power supply, 1U, standard 19-inch rack-mounted installation)                                                                                      |
| <b>TR-S5754</b>            | Multi-Gigabit Ethernet routing switch with (1 RJ45 CLI port, 1 out-band optical port, 48 2.5G/GE TX ports, 4x10G/GE SFP+ ports, 2x40G QSFP ports; dual hot-swap power slots with single AC220V power supply; fan cooling, 1U, standard 19-inch rack-mounted installation) |

Copyright ©Techroutes Network Pvt Ltd. 2025.All Rights Reserved. This document is Techroutes Network Public Information. Techroutes Network reserves the right to alter, update and otherwise change the information contained in the document from time to time.



**For More details:**

visit: [www.techroutes.com](http://www.techroutes.com)

Or contact

[sales@techroutes.com](mailto:sales@techroutes.com)

[info@techroutes.com](mailto:info@techroutes.com)